

# MAIT -HR 180 CP



## Technical Specs

### WORKING CHARACTERISTICS

#### Works with Augers & Buckets:

Max diameter	500 / 1.600 mm	1.6 / 5.2 ft
Without lower mast extension	2.000 mm	6.5 ft
Depths	30 - 40 - 50 - 60 m	98.5 - 131 - 164 - 197 ft

#### Casing Oscillator:

Max. diameter	1.600 mm	5.2 ft
---------------	----------	--------

#### Works with CFA:

Max. diameter	1.200 mm	4 ft
Depths	19 + 5 m	62 + 16 ft

#### Diaphragm Walling:

Max size	1.000 x 2.500 mm	3.3 x 8 ft
Depths	32 m	105 ft

**Jet Grouting:**

Max depth	32 m	105 ft
-----------	------	--------

## TECHNICAL DATA

**Rotary:**

Nominal torque	233 KNm	171,900 lbsft
----------------	---------	---------------

Rotary nominal pulldown	180 KN	40,500 lbs
-------------------------	--------	------------

Unloading speed	150 rpm	
-----------------	---------	--

Rotary stroke	5.100 mm	17 ft
---------------	----------	-------

**Winches:**

Main winch nominal pullback	180 KN	40,500 lbs
-----------------------------	--------	------------

Auxiliary winch nominal pullback	80 KN	18,000 lbs
----------------------------------	-------	------------

**Diesel Engine: CATERPILLAR C9 ACERT**

Power	242 KW	325 HP
-------	--------	--------

Hydraulic installation	5 pumps	
------------------------	---------	--

Hydraulic oil tank	800 litres	211 gal
--------------------	------------	---------

Fuel tank	430 litres	114 gal
-----------	------------	---------

**Expandable Crawlers:**

Lenght	4.900 mm	16 ft
--------	----------	-------

Width	3.000 - 4.300 mm	9.5 ft - 14 ft
-------	------------------	----------------

Shoes	800 mm	2.6 ft
-------	--------	--------

<b>Approx. Weight:</b>	57-60 tons	128,600 - 132,500 lbs
------------------------	------------	-----------------------